



3" x4" [76mm x102mm] VENTED RUBBER BASE.

25/32" x2-1/4" [20mm x57mm] ACTION HARD MAPLE FLOORING.

2" [50mm] FLOORING FASTENERS.

3/8" [10mm] ACTIONCUSH PAD OR 7/16" [11mm] AIRTECH II NATURAL RUBBER PADS - 12" [300mm] O.C.

CONCRETE SLAB.

6-MIL. POLYETHYLENE FILM (TYPICAL).

15/32" [12mm] SUBFLOOR, EXPOSURE 1, RATED SHEATHING, MINIMUM APA SPAN RATING OF 32/16.

1-1/2" x2-1/2" x8'-0" [38mm x64mm x2.4m] SLEEPERS, NOMINAL, EXPOSURE 1, RATED SHEATHING, MINIMUM APA SPAN RATING OF 32/16, OPTIONAL: 2 x3 x8'-0" [38mm x64mm x2.4m] NOMINAL SPF SLEEPER SPACED 9" [229mm] O.C. USING 25/32 [20mm] FLOORING, OR SPACED 12" [300mm] O.C. USING 33/32" [27mm] FLOORING.

ELECTRICAL OUTLETS (SUPPLIED BY OTHERS).

FLUSH PLATE COVER FOR ELECTRICAL OUTLETS OR SLEEVES (SUPPLIED BY OTHERS).

2" [50mm] EXPANSION SPACE.

6" [150mm] ALUMINUM EXPANSION PLATE.

25/32" [20mm]

3 1/8" [80mm]

2 3/8" [60mm]

ActionCush II Plus

201511.20