

LED Racquetball Court 14.5" x 48"



Frame Out Flange Mount

- Energy saving alternative to HID
- Flange or frame out mounting option
- Tempered, obscure, glass lens with flush fit trim
- High color rendering for enhanced visibility
- Philips Fortimo HI Flux LED Modules
- Osram OPTOTRONIC power supplies
- Service life >100,000 hrs. (L90)
- Magnum wireless protocol option
- Made in the USA, 10 year warranty

Wattage & Lumen Packages

- 94 watts @ 9,517 lumens (recreational)
- 117 watts @ 12,075 lumens (standard)
- 141 watts @ 13,916 lumens (competition)

Specifications

- Philips Fortimo Hi Flux LED Modules, 80 + CRI, 3000K, 3500K, 4000K or 5000K.
- Osram Optotronic LED Power Supply, 120-277v or 347v, 480v available with transformer.
- Low voltage dimming capability down to 0 or 10% (specify if dimming leads are required).
- Optional motion sensor, magnum wireless controls, A/B switching, emergency ballast.
- All control systems are pre-commissioned at factory for seamless integration during install.

Construction

- 0.40" white pre-painted aluminum with top access plate.
- Flush fit trim piece for true rebound during play.
- Frame out or flange mounting options.
- 3/16" obscured tempered glass eliminates glare.
- Bottom access door frame with secure latch.
- Top access plate provided for easy power connection.
- 100% bench tested prior to shipping.
- All fixtures are made in the USA.

Ratings

- Operating Temperature: -28°C to 50°C (-20°F/122°F)
- Rated service life > 100,000 hours (L90)
- No mercury, RoHS compliant, DLC listed and CSA approved